




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : A61B 5/00, 5/05	A1	(11) International Publication Number: WO 99/08588 (43) International Publication Date: 25 February 1999 (25.02.99)
<p>(21) International Application Number: PCT/US98/16976</p> <p>(22) International Filing Date: 17 August 1998 (17.08.98)</p> <p>(30) Priority Data: 08/912,331 18 August 1997 (18.08.97) US</p> <p>(71) Applicants: LUCID, INC. [US/US]; 235 Middle Road, Henrietta, NY 14467 (US). THE GENERAL HOSPITAL CORPORATION [-/US]; 55 Fruit Street, Boston, MA 02114 (US).</p> <p>(72) Inventors: GREENWALD, Roger, J.; 16787 Ridge Road, Holley, NY 14470 (US). RAJADHYASKSHA, Milind; Apartment 3112, 42 Eight Street, Charlestown, MA 02129 (US).</p> <p>(74) Agent: LUKACHER, Kenneth, J.; Harris Beach & Wilcox, LLP, 130 East Main Street, Rochester, NY 14604-1687 (US).</p>	<p>(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, HR, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).</p> <p>Published With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</p>	

(54) Title: SYSTEM FOR IMAGING MECHANICALLY STABILIZED TISSUE



(57) Abstract

A system (8) is provided having a clamping apparatus (10) with a first member (12) and a second member (14), which are spaced apart from each other. An attachment mechanism (20) is connected to the first member (12) for attaching the apparatus (10) to a confocal imaging system (22). This attachment mechanism (20) has a surface with a window facing the tissue to be examined. Opposing this surface is a third member (40) connected to the second member (14). A clamping mechanism includes the first member (12) and the second member (14) for clamping the tissue between the surface of the attachment mechanism (20) and the surface of the third member (40), thereby stabilizing the tissue to the confocal imaging system (22). The window (32) of the attachment mechanism (20) presents the clamped tissue to the confocal imaging system (22).

BEST AVAILABLE COPY

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakistan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

SYSTEM FOR IMAGING MECHANICALLY STABILIZED TISSUE

Description

Field of the Invention

The present invention relates to an imaging system for in vivo examinations of tissues, and particularly to a confocal imaging system operative upon the tissue of a patient body part or animal subject which mechanically stabilizes the tissue to minimize instability in confocal images of the tissue. This invention is especially suitable for providing an instrument or attachment for pathological applications.

This application is related to European Patent Publication EP0821256A2, published 28 January 1998, and entitled Three-Dimensional Scanning Confocal Laser Microscope.

Background of the Invention

Systems have been proposed for confocal scanning of skin, such as described in an article by Rajadhyaksha et al., entitled "In vivo Confocal Scanning Laser Microscopy of Human Skin: Melanin provides strong contrast," The Journal of Investigative Dermatology, Volume 104, No. 6, June 1995, pages 1-7, and also Rajadhyaksha et al., entitled "Confocal laser microscope images tissue in vivo," Laser Focus World, February 1997, page 119-127. These systems have confocal optics which direct light to the patient's skin tissue and image the returned reflected light. Such optics has a limited field of view of the patient's skin tissue, which for example may cover a tissue area less than one millimeter wide. One problem with these systems is that motion of the patient during confocal imaging can cause the tissue area being imaged to move relative to the system's confocal optics, shifting the field of view of the tissue area with respect to the optics. Consequently, confocal images from such systems may appear unstable to the viewing physician, making it difficult for the physician to observe dermal structures of interest. Even slight motion of the patient's skin tissue, such as due to involuntary muscle movement in adjacent tissue or from a circulatory pulse, can cause dermal structures of a confocal image to appear to move in and out of the imaged tissue area. The confocal optics may also image other types of patient tissue in addition to dermal tissues, for example, oral tissue of the tongue

or lip, but motion of such tissue can still cause instability in confocal images of tissue structures.

Summary of the Invention

Accordingly, it is the principal feature of the present invention to provide an improved system for confocal imaging of tissue of a patient which minimizes instability in confocal images by reducing the relative motion of the tissue with respect to the confocal imaging optics of the system.

It is another feature of the present invention to provide an improved system for confocal imaging having a clamping apparatus which mechanically stabilizes the tissue to a confocal imaging system within the improved system.

Briefly described, the present invention embodies a system having a clamping apparatus with first and second members, which are spaced apart from each other. An attachment mechanism is connected to the first member for attaching the apparatus to a confocal imaging system. The attachment mechanism has a surface facing the tissue to be examined. Opposing this surface is a third member which is connected to the second member. A clamping mechanism includes the first and second members for clamping the tissue between the surface of the attachment mechanism and the surface of the third member. A window is provided in the surface of the attachment mechanism for presenting the clamped tissue to the confocal imaging system.

The clamping mechanism may include a turn screw threaded through the first and second members, or a pneumatic system, for clamping the apparatus to the tissue. An optional suction mechanism may be used to assist in clamping the tissue to the attachment mechanism.

Brief Description of the Drawings

The foregoing features and advantages of the invention will become more apparent from a reading of the following description in connection with the accompanying drawings in which:

FIG. 1 is a side elevational view of the system of the present invention showing a clamping apparatus attached to a confocal imaging system;

FIG. 2 is a top view of the clamping apparatus of FIG. 1;

- 3 -

FIG. 3 is a perspective view from the bottom of the clamping apparatus of FIGS. 1 and 2;

FIG. 4 is a perspective view from the top of the clamping apparatus of FIGS. 1 and 2;

FIGS. 5A and 5B are side views of the clamping apparatus of FIG. 1 showing an example of the apparatus before and after being clamped to tissue, respectively;

FIG. 6 is a perspective view from the bottom of the clamping apparatus of FIGS. 1 and 2 showing an optional suction mechanism to assist in clamping tissue;

FIGS. 7A and 7B are side views of the clamping apparatus similar to FIG. 1 showing a clamping mechanism with a pneumatic system before and after the bladder of the pneumatic system is inflated, respectively, to clamp the apparatus to tissue; and

FIGS. 8A, 8B and 8C are perspective views from the top of the clamping apparatus of FIG. 5B showing a biopsy device before, during and after taking a biopsy of the clamped tissue through the apparatus, respectively.

Detailed Description of the Invention

Referring to FIGS. 1-4, a system 8 includes a clamping apparatus 10 having a first member 12 and a second member 14 which is spaced apart from the first member. Member 12 has a lower surface 16 opposing an upper surface 18 of member 14. At one end of member 12 is connected a mechanism 20 for attaching or coupling apparatus 10 to a confocal imaging system 22 of system 8. For purposes of illustration, confocal imaging system 22 is represented by a cylinder 23 which contains confocal optics, such as an objective focusing lens. Confocal imaging system 22 is described in related European Patent Publication EP0821256A2, published 28 January 1998. While confocal imaging is the preferred embodiment, system 22 may also represent a system using other imaging modalities, such as optical coherence tomography, described for example in Schmitt et al., "Optical characterization of disease tissues using low-coherence interferometry," Proc. of SPIE, Volume 1889 (1993), or two-photon microscopy, described for example in U.S. Patent No. 5,034,613, to Denk et al., or deconvolution confocal microscopy, described for example in Kesterson, et al., "Confocal Microscope Capability with Desktop Affordability," Advanced Images, Oct. 1991, pages 23-24, or fluorescent imaging. The

objective focusing lens in system 22 may be part of a fixed station or a portable confocal imaging system.

Mechanism 20 has an annular receptacle 24, such as a ring, having a lower member or template 28. Receptacle 24 receives cylinder 23, while pins 26, for example three, are threaded into the sides of receptacle 24, such that they can be extended into grooves or openings 27 in cylinder 23, thereby fixing the position of the confocal imaging system 22 to apparatus 10. (Openings 27 and cylinder 23 are shown in receptacle 24 of FIG. 1 as dashed lines.) Mechanism 20 is described, for example, in related European Patent Publication EP0821256A2, published 28 January 1998. Template 28 has an aperture 30 through which the confocal imaging system, i.e., confocal optics, images the tissue. Aperture 30 may, for example, be several millimeters in diameter. As best shown in FIG. 3, an annular recess 34 in the bottom surface 29 of template 28 is in communication with aperture 30, in other words, a bore of smaller to larger diameter from aperture 30 and recess 34, respectively, widens to provide an annular recess 34 at surface 29. (Recess 34 is also shown in dotted lines in FIG. 2.) In recess 34, a window 32 of a thin transparent material, such as plastic or glass, is fitted. For example, window 32 may be a thin plate of glass, suitably about 0.1-0.2 mm thick. Window 32 is sized such that it fits into annular recess 34, however, window 32 may be square in shape, thus requiring grooves in recess 34 to receive the corners of the window. Window 32, for example, may be a coverslip as conventionally used in preparation of slides for a typical optical microscope. Surface 29 of template 28 has a textured surface, which is represented by raised ridges 36.

In apparatus 10, an opposing member 40 has an upper surface 41 which opposes surface 29 of mechanism 20. Opposing member 40 is connected to an end 14b of member 14. Upper surface 41 has a textured surface, which is represented by raised ridges 38 (see FIG. 4). Surface 41 optionally may have a layer of deformable compliant material, such as urethane. Member 40 may be a disk, as illustrated in the figures, however the shape of member 40 may depend on the patient body part having the tissue to be located between surfaces 29 and 41. For example, member 40 may be split into two or more sections, like a fork, to avoid interfering with other tissue near the body part, such as when the tissue to be imaged is in the middle of the tongue. Other shapes for member 40 may also be used, such as oblong or rectangle. Accordingly, member 40 may be any structure providing a

- 5 -

surface 41 which opposes surface 29 and can provide pressure and traction against a patient body part clamped between surfaces 29 and 41, as described below. Members 12 and 14, receptacle 24, and member 40 may be made of stainless-steel or plastic. Receptacle 24 may be a separate component that is joined (screwed or welded) to the assembly of member 12.

A clamping mechanism in apparatus 10 clamps tissue in the space between surface 29 of mechanism 20 and surface 41 of member 40. The clamping mechanism includes a hinge provided by a spring 42 to members 12 and 14 at the ends thereof opposite mechanism 20 and member 40, respectively, a turn screw 44 threaded in holes 12a and 14a through members 12 and 14, respectively, and members 12 and 14 connected to mechanism 20 and member 40, respectively. Spring 42 is a flat strip of flexible material (steel, plastic or bronze), and applies a force on members 12 and 14 pushing the members apart from each other. Screw 44 is rotatable to manually adjust the spacing between surfaces 29 and 41, such that tissue can be clamped between surfaces 29 and 41, and released therefrom. Alternatively, the clamping mechanism may be provided by two or more screws, similar to screw 44, threaded through members 12 and 14 for setting the space between surfaces 29 and 41. These screws can be independently adjusted to provide angular adjustment of members 12 and 14 to each other to insure that surfaces 29 and 41 are parallel as they restrain the tissue. Other means for clamping may also be used which are similar to clamps of conventional surgical instruments.

Referring to the example shown in FIGS. 5A and 5B, a tongue 46 having the tissue of a patient to be examined is first inserted between members 12 and 14. To facilitate insertion of tongue 46, an operator turns screw 44 until the space between surfaces 29 and 41 is wider than the thickness of the tongue. With tongue 46 between surfaces 29 and 41 and the area of the tongue to be investigated facing window 32, the tongue is clamped to apparatus 10 by the operator turning screw 44 until the tongue is immobilized with respect to surfaces 29 and 41 without damaging the tissue or causing unnecessary discomfort to the patient. The textured surfaces of surfaces 29 and 41 provide traction against the surfaces of tongue 46 to maintain the tissue area under investigation stable for imaging. When apparatus 10 is clamped to tongue 46, surfaces 29 and 41 of mechanism 20 and member 40, respectively, are substantially parallel to each other. Accordingly, the

- 6 -

downward clamping force of mechanism 20 is substantially parallel to the upward clamping force of member 40 against the surfaces of tongue 46. This is an important feature of the invention since it avoids the tongue from squeezing out of clamping apparatus 10.

The confocal imaging system 22 is attached into receptacle 24 of mechanism 20 using pins 26, as shown in FIG. 1, to provide an integrated assembly of the imaging system 22 and apparatus 10. The attachment may be done most conveniently after the tissue is clamped by apparatus 10, however it may occur before tongue 46 is clamped. Window 32 in surface 29 of mechanism 20 presents a tissue area of the clamped tongue to the confocal imaging optics in system 22, thereby enabling confocal imaging of the tissue beneath the window. The tissue under the window is thus mechanical stabilized to the confocal imaging system 22, which minimize instability in confocal images by reducing the relative motion of tissue with respect to the confocal imaging optics of system 22. Apparatus 10 may also operate without window 32, such that window 32 is removed from recess 34 prior to apparatus 10 being clamped to tissue.

Optionally, a suction mechanism may assist in clamping apparatus 10 to tongue 46, as shown in FIG. 6. The suction mechanism includes a syringe 50 connected through a hose 52 to receptacle 24. An annular opening, or one or more holes, provided in surface 29 of receptacle 24 is in communication with hose 52, such that after apparatus 10 is clamped to tongue 46, pulling plunger 51 of syringe 50 in the direction of arrow 53 suctions any air between surface 29 and the surface of tongue 46 facing surface 29. This results in a vacuum adhering surface 29 and the clamped tissue together, thereby further stabilizing the tongue against window 32.

Referring to FIGS. 7A and 7B, clamping apparatus 10 is shown in which the clamping mechanism is provided by a pneumatic system instead of turn screw 44 (FIG. 1), and members 12 and 14 are part of a single C-shaped member 13 without hinge 42. The pneumatic system includes a bladder 54, which is attached to surface 41, a syringe 58, and a hose 56 connecting syringe 58 to bladder 54. A fluid 57, such as air, water, or the like, can pass through hose 56 between bladder 54 and a cavity 60 in syringe 58. Cavity 60 is defined by the interior of syringe 58 and the head 63 of a plunger 62 in syringe 58.

- 7 -

Plunger 62 is slidable within syringe 58 to change the volume of fluid 57 in both cavity 60 and bladder 54.

As shown in FIG. 7A, when plunger 62 is in a first position, bladder 54 is deflated due to the lack of fluid 57 in bladder 54. In this first position, the tissue, such as tongue 46 of FIG. 5A, may be inserted between mechanism 20 and member 40. Once the tissue is properly positioned under mechanism 20, plunger 62 is pushed by an operator to a second position, as shown in FIG. 7B. This forces some of the fluid 57 in cavity 60 through hose 56 into bladder 54, which causes bladder 54 to inflate and force the tissue against surface 29. Bladder 54 is inflated to sufficiently clamp apparatus 10 to the tissue. Hose 56 may be clamped if needed to prevent back flow of fluid 57 into cavity 60 of syringe 58. Optionally, single or multiple turn screws 44 (FIG. 1) may be used in apparatus 10 in combination with the pneumatic system in which bladder 54, when inflated, provides an additional clamping force upon the tissue.

System 8 is particularly useful for mechanically stabilizing the confocal imaging system 22 to oral tissue, such as the tongue or lip, which may have mucus on its surface. However, apparatus 10 may be sized to accommodate clamping of other tissues of the patient to mechanism 20, such as fingers, the palm of a hand, nails, ears, or male genitalia.

After imaging by confocal system 22, the tissue is released from apparatus 10 by turning turn screw 44 (FIG. 1) in a direction which moves member 40 and mechanism 20 apart from each other, or if the pneumatic system of FIGS. 7A and 7B is used, the tissue is released by pulling plunger 62 back to its first position to deflate bladder 54. However, before the tissue is released from apparatus 10, a biopsy device 64 can be inserted into receptacle 24 to take a biopsy 46(a) of the tissue under window 32, as shown in FIGS. 8A-8C. The biopsy device 64 has a projection 66 which, when positioned in receptacle 24 (FIG. 8B), cuts through window 32 and into the tissue under window 32. However, window 32 may be removed from recess 34 prior to the clamping of apparatus 10 to tissue, such that biopsy device 64 will not need to cut window 32. Blade(s) (not shown) in projection 66 are then extended to cut beneath the tissue surface. As device 64 is removed from receptacle 24 (FIG. 8C) an excised biopsy 46(a) is provided. This biopsy can then be examined by typical pathological techniques to confirm any tissue abnormalities found during imaging of the tissue.

- 8 -

From the foregoing description, it will be apparent that there has been provided an improved system for confocal imaging in tissue. Variations and modifications in the herein described system in accordance with the invention will undoubtedly suggest themselves to those skilled in the art. For example, members 12 and 14, tissue engaging parts 20 and 40, and even spring 42, may be an integrated body molded from plastic or stainless steel. Accordingly, the foregoing description should be taken as illustrative and not in a limiting sense.

What is claimed is:

1. A system for imaging mechanically stabilized tissue comprising:
means for clamping the tissue by application of force to said tissue; and
an imaging system for imaging at least a portion of the clamped tissue coupled to said clamping means to provide therewith an integrated assembly.
2. The system according to Claim 1 wherein said clamping means comprises:
a first member and a second member spaced apart and opposing said first member;
and
means coupled to said first member for attaching said first member to said imaging system.
3. The system according to Claim 2 wherein said attaching means has a first surface facing said tissue, and said clamping means further comprises a third member, coupled to said second member, having a second surface opposing said first surface of said attaching means.
4. The system according to Claim 3 wherein said clamping means further comprises means for adjusting the spacing between said first and second surfaces to force said first and second surfaces against the surfaces of said tissue, thereby clamping said tissue between said first and second surfaces without damaging said tissue.
5. The system according to Claim 4 wherein said adjusting means further comprises means for adjusting the spacing between said first and second surfaces to release said clamped tissue from between said first and second surfaces.
6. The system according to Claim 4 wherein said first and second surfaces are substantially parallel to each other when said first and second surface are clamped to said tissue.

- 10 -

7. The system according to Claim 4 wherein said adjusting means is provided by at least one screw threaded through holes in said first and second members which is rotatable to adjust the spacing between said first and second surfaces.

8. The system according to Claim 3 wherein said clamping means further comprises:

means for inflating a bladder from said second surface of said third member against said tissue to force said tissue against said first surface, thereby clamping said tissue between said first and second surfaces without damaging said tissue.

9. The system according to Claim 8 wherein said bladder is inflated with a fluid sufficient to force said tissue against said first surface.

10. The system according to Claim 9 wherein said inflating means further comprises means for deflating said bladder of said fluid sufficient to release said clamped tissue from between said first and second surfaces.

11. The system according to Claim 9 wherein said fluid is one of liquid and gas.

12. The system according to Claim 3 wherein said second surface has a deformable material facing said tissue.

13. The system according to Claim 3 wherein said first and second surfaces are textured.

14. The system according to Claim 3 wherein said clamping means further comprises means for suctioning air from between said first surface and the surface of said tissue facing said first surface to adhere said first surface to the surface of said tissue.

- 11 -

15. The system according to Claim 3 wherein said third member has one or more sections providing said second surface, said sections being shaped to avoid interference of said clamping means with other tissue near said tissue when said tissue is clamped between said first and second surfaces.

16. The system according to Claim 3 wherein said first and second members are parts of a single member having a closed end in which said closed end opposes said tissue when said tissue is clamped between said first and second surfaces.

17. The system according to Claim 3 wherein said clamping means further comprises a hinge, coupled to said first and second members, which opposes said tissue when said tissue is clamped between said first and second surfaces.

18. The system according to Claim 2 wherein said attaching means comprises a receptacle, coupled to said first member, which is attachable to said imaging system, said receptacle having a template facing said tissue and an aperture in said template through which said imaging system images said clamped tissue when said imaging system is attached to said receptacle.

19. The system according to Claim 18 wherein said template has a recess in communication with said aperture.

20. The system according to Claim 19 wherein said receptacle has a window of a thin transparent material fitted in said recess.

21. The system according to Claim 18 further comprising means for taking a biopsy of said clamped tissue through said aperture when said imaging system is detached from said receptacle.

22. The system according to Claim 1 wherein said imaging system is a confocal imaging system for displaying images of sections of said clamped tissue.

- 12 -

23. An apparatus for positioning tissue to an imaging system comprising:
a first member and a second member spaced apart and opposing said first member;
means coupled to said first member for attaching said apparatus to said imaging system, said attaching means having a first surface facing said tissue;
a third member coupled to said second member having a second surface opposing said first surface of said attaching means; and
means including said first and second members for clamping the tissue between said first and second surfaces.

24. The apparatus according to Claim 23 wherein said clamping means further comprises means for adjusting the spacing between said first and second surfaces to force said first and second surfaces against the surfaces of said tissue, thereby clamping said tissue between said first and second surfaces without damaging said tissue.

25. The apparatus according to Claim 24 wherein said adjusting means further comprises means for adjusting the spacing between said first and second surfaces to release said clamped tissue from between said first and second surfaces.

26. The apparatus according to Claim 24 wherein said first and second surfaces are substantially parallel to each other when said first and second surface are clamped to said tissue.

27. The apparatus according to Claim 24 wherein said adjusting means is provided by at least one screw threaded through holes in said first and second members which is rotatable to adjust the spacing between said first and second surfaces.

28. The apparatus according to Claim 23 wherein said clamping means further comprises:

means for inflating a bladder from said second surface of said third member against said tissue to force said tissue against said first surface, thereby clamping said tissue between said first and second surfaces without damaging said tissue.

- 13 -

29. The apparatus according to Claim 28 wherein said bladder is inflated with a fluid sufficient to force said tissue against said first surface.

30. The apparatus according to Claim 29 wherein said inflating means further comprises means for deflating said bladder of said fluid sufficient to release said clamped tissue from between said first and second surfaces.

31. The apparatus according to Claim 29 wherein said fluid is one of liquid and gas.

32. The apparatus according to Claim 23 wherein said second surface has a deformable material facing said tissue.

33. The apparatus according to Claim 23 wherein said first and second surfaces are textured.

34. The apparatus according to Claim 23 wherein said clamping means further comprises means for suctioning air from between said first surface and the surface of said tissue facing said first surface to adhere said first surface to the surface of said tissue.

35. The apparatus according to Claim 23 wherein said third member has one or more sections providing said second surface, said sections being shaped to avoid interference of said clamping means with other tissue near said tissue when said tissue is clamped between said first and second surfaces.

36. The apparatus according to Claim 23 wherein said first and second members are parts of a single member having a closed end in which said closed end opposes said tissue when said tissue is clamped between said first and second surfaces.

- 14 -

37. The apparatus according to Claim 23 wherein said clamping means further comprises a hinge, coupled to said first and second members, which opposes said tissue when said tissue is clamped between said first and second surfaces.

38. The apparatus according to Claim 23 wherein said attaching means further comprises a receptacle, coupled to said first member, which is attachable to said imaging system, said receptacle having a template facing said tissue and an aperture in said template through which said imaging system images said clamped tissue when said imaging system is attached to said receptacle.

39. The apparatus according to Claim 38 wherein said template has a recess in communication with said aperture.

40. The apparatus according to Claim 39 wherein said receptacle has a window of a thin transparent material which is fitted in said recess.

41. The apparatus according to Claim 38 further comprising means for taking a biopsy of said clamped tissue through said aperture when said imaging system is detached from said receptacle.

42. The apparatus according to Claim 23 wherein said imaging system is a confocal imaging system for displaying images of sections of said clamped tissue.

43. A method for positioning tissue to an imaging system comprising the steps of:

providing a first member and a second member which is spaced apart and opposes said first member;

coupling said first member to said imaging system with the aid of a receptacle attachable to said imaging system, in which said receptacle presents a first surface facing said tissue;

- 15 -

coupling said second member to a third member which presents a second surface opposing said first surface; and

clamping the tissue between said first and second surfaces in which said imaging system images said clamped tissue through an aperture in said receptacle when said imaging system is attached to said receptacle.

44. The method according to Claim 43 wherein said clamping step further comprises the step of:

adjusting the spacing between said first and second surfaces to force said first and second surfaces against the surfaces of said tissue without damaging said tissue.

45. The method according to Claim 43 wherein said first and second surfaces are substantially parallel to each other when said first and second surface are clamped to said tissue.




FIG. 1





FIG. 2






FIG. 4




FIG. 5A




FIG. 5B




FIG. 6




FIG. 7A




FIG. 7B




FIG. 7A




FIG. 7B




FIG. 7C

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US98/16976

A. CLASSIFICATION OF SUBJECT MATTER

IPC(6) :A61B 5/00, 5/05

US CL :600/407

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 600/407, 415, 425, 587, 417, 421, 429, 473, 476; 378/37, 62, 63, 195; 128/915

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

NONE

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

APS

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X, P ----- Y, P	US 5,730,133 A (GODIK) 24 March 1998, see entire document.	1, 3 ----- 2, 4-7, 13, 14, 17-20, 23-26, 32, 33, 36, 37-39, 42, 43-45
Y	US 4,212,306 A (MAHMUD) 15 July 1980, see entire document.	2, 4-7, 13, 14, 17-20, 23-26, 32, 33, 36, 37-39, 42, 43-45
Y	US 5,056,523 A (HOTCHKISS, JR. et al.) 15 October 1991, see entire document.	22, 41

☒ Further documents are listed in the continuation of Box C. ☐ See patent family annex.

* Special categories of cited documents:	*T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
A document defining the general state of the art which is not considered to be of particular relevance	*X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
E earlier document published on or after the international filing date	*Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	*Z* document member of the same patent family
O document referring to an oral disclosure, use, exhibition or other means	
P document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search

17 SEPTEMBER 1998

Date of mailing of the international search report

22 DEC 1998

Name and mailing address of the ISA/US
Commissioner of Patents and Trademarks
Box PCT
Washington, D.C. 20231

Facsimile No. (703) 305-3230

Authorized officer

BRIAN L. CASLER

Telephone No. (703) 306-3490

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US98/16976


C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 4,774,961 A (CARR) 04 October 1988.	1-45
A	US 5,371,368 A (ALFANO et al.) 06 December 1994.	1-45
A, P	US 5,772,597 A (GOLDBERGER et al.) 30 June 1998.	1-45

Form PCT/ISA/210 (continuation of second sheet)(July 1992)★



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : A61B 5/00, 5/05	A1	(11) International Publication Number: WO 99/08588 (43) International Publication Date: 25 February 1999 (25.02.99)
(21) International Application Number: PCT/US98/16976 (22) International Filing Date: 17 August 1998 (17.08.98) (30) Priority Data: 08/912,331 18 August 1997 (18.08.97) US (71) Applicants: LUCID, INC. [US/US]; 235 Middle Road, Henrietta, NY 14467 (US). THE GENERAL HOSPITAL CORPORATION[US/US]; 55 Fruit Street, Boston, MA 02114 (US). (72) Inventors: GREENWALD, Roger, J.; 16787 Ridge Road, Holley, NY 14470 (US). RAJADHYASKSHA, Milind; Apartment 3112, 42 Eight Street, Charlestown, MA 02129 (US). (74) Agent: LUKACHER, Kenneth, J.; Harris Beach & Wilcox, LLP, 130 East Main Street, Rochester, NY 14604-1687 (US).		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, HR, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>
(54) Title: SYSTEM FOR IMAGING MECHANICALLY STABILIZED TISSUE  (57) Abstract <p>A system (8) is provided having a clamping apparatus (10) with a first member (12) and a second member (14), which are spaced apart from each other. An attachment mechanism (20) is connected to the first member (12) for attaching the apparatus (10) to a confocal imaging system (22). This attachment mechanism (20) has a surface with a window facing the tissue to be examined. Opposing this surface is a third member (40) connected to the second member (14). A clamping mechanism includes the first member (12) and the second member (14) for clamping the tissue between the surface of the attachment mechanism (20) and the surface of the third member (40), thereby stabilizing the tissue to the confocal imaging system (22). The window (32) of the attachment mechanism (20) presents the clamped tissue to the confocal imaging system (22).</p>		

*(Referred to in PCT Gazette No. 18/1999, Section II)

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		




PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : A61B 5/00, 5/05		A1	(11) International Publication Number: WO 99/08588
			(43) International Publication Date: 25 February 1999 (25.02.99)
(21) International Application Number: PCT/US98/16976		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, HR, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).	
(22) International Filing Date: 17 August 1998 (17.08.98)		<p>Published</p> <p><i>With international search report.</i></p> <p><i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i></p>	
(30) Priority Data: 08/912,331 18 August 1997 (18.08.97) US			
(71) Applicants: LUCID, INC. [US/US]; 235 Middle Road, Henrietta, NY 14467 (US). THE GENERAL HOSPITAL CORPORATION[US/US]; 55 Fruit Street, Boston, MA 02114 (US).			
(72) Inventors: GREENWALD, Roger, J.; 16787 Ridge Road, Holley, NY 14470 (US). RAJADHYASKSHA, Milind; Apartment 3112, 42 Eight Street, Charlestown, MA 02129 (US).			
(74) Agent: LUKACHER, Kenneth, J.; Harris Beach & Wilcox, LLP, 130 East Main Street, Rochester, NY 14604-1687 (US).			

(54) Title: SYSTEM FOR IMAGING MECHANICALLY STABILIZED TISSUE



(57) Abstract

A system (8) is provided having a clamping apparatus (10) with a first member (12) and a second member (14), which are spaced apart from each other. An attachment mechanism (20) is connected to the first member (12) for attaching the apparatus (10) to a confocal imaging system (22). This attachment mechanism (20) has a surface with a window facing the tissue to be examined. Opposing this surface is a third member (40) connected to the second member (14). A clamping mechanism includes the first member (12) and the second member (14) for clamping the tissue between the surface of the attachment mechanism (20) and the surface of the third member (40), thereby stabilizing the tissue to the confocal imaging system (22). The window (32) of the attachment mechanism (20) presents the clamped tissue to the confocal imaging system (22).

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

SYSTEM FOR IMAGING MECHANICALLY STABILIZED TISSUE

Description

Field of the Invention

The present invention relates to an imaging system for in vivo examinations of tissues, and particularly to a confocal imaging system operative upon the tissue of a patient body part or animal subject which mechanically stabilizes the tissue to minimize instability in confocal images of the tissue. This invention is especially suitable for providing an instrument or attachment for pathological applications.

This application is related to European Patent Publication EP0821256A2, published 28 January 1998, and entitled Three-Dimensional Scanning Confocal Laser Microscope.

Background of the Invention

Systems have been proposed for confocal scanning of skin, such as described in an article by Rajadhyaksha et al., entitled "In vivo Confocal Scanning Laser Microscopy of Human Skin: Melanin provides strong contrast," The Journal of Investigative Dermatology, Volume 104, No. 6, June 1995, pages 1-7, and also Rajadhyaksha et al., entitled "Confocal laser microscope images tissue in vivo," Laser Focus World, February 1997, page 119-127. These systems have confocal optics which direct light to the patient's skin tissue and image the returned reflected light. Such optics has a limited field of view of the patient's skin tissue, which for example may cover a tissue area less than one millimeter wide. One problem with these systems is that motion of the patient during confocal imaging can cause the tissue area being imaged to move relative to the system's confocal optics, shifting the field of view of the tissue area with respect to the optics. Consequently, confocal images from such systems may appear unstable to the viewing physician, making it difficult for the physician to observe dermal structures of interest. Even slight motion of the patient's skin tissue, such as due to involuntary muscle movement in adjacent tissue or from a circulatory pulse, can cause dermal structures of a confocal image to appear to move in and out of the imaged tissue area. The confocal optics may also image other types of patient tissue in addition to dermal tissues, for example, oral tissue of the tongue

or lip, but motion of such tissue can still cause instability in confocal images of tissue structures.

Summary of the Invention

Accordingly, it is the principal feature of the present invention to provide an improved system for confocal imaging of tissue of a patient which minimizes instability in confocal images by reducing the relative motion of the tissue with respect to the confocal imaging optics of the system.

It is another feature of the present invention to provide an improved system for confocal imaging having a clamping apparatus which mechanically stabilizes the tissue to a confocal imaging system within the improved system.

Briefly described, the present invention embodies a system having a clamping apparatus with first and second members, which are spaced apart from each other. An attachment mechanism is connected to the first member for attaching the apparatus to a confocal imaging system. The attachment mechanism has a surface facing the tissue to be examined. Opposing this surface is a third member which is connected to the second member. A clamping mechanism includes the first and second members for clamping the tissue between the surface of the attachment mechanism and the surface of the third member. A window is provided in the surface of the attachment mechanism for presenting the clamped tissue to the confocal imaging system.

The clamping mechanism may include a turn screw threaded through the first and second members, or a pneumatic system, for clamping the apparatus to the tissue. An optional suction mechanism may be used to assist in clamping the tissue to the attachment mechanism.

Brief Description of the Drawings

The foregoing features and advantages of the invention will become more apparent from a reading of the following description in connection with the accompanying drawings in which:

FIG. 1 is a side elevational view of the system of the present invention showing a clamping apparatus attached to a confocal imaging system;

FIG. 2 is a top view of the clamping apparatus of FIG. 1;

FIG. 3 is a perspective view from the bottom of the clamping apparatus of FIGS. 1 and 2;

FIG. 4 is a perspective view from the top of the clamping apparatus of FIGS. 1 and 2;

FIGS. 5A and 5B are side views of the clamping apparatus of FIG. 1 showing an example of the apparatus before and after being clamped to tissue, respectively;

FIG. 6 is a perspective view from the bottom of the clamping apparatus of FIGS. 1 and 2 showing an optional suction mechanism to assist in clamping tissue;

FIGS. 7A and 7B are side views of the clamping apparatus similar to FIG. 1 showing a clamping mechanism with a pneumatic system before and after the bladder of the pneumatic system is inflated, respectively, to clamp the apparatus to tissue; and

FIGS. 8A, 8B and 8C are perspective views from the top of the clamping apparatus of FIG. 5B showing a biopsy device before, during and after taking a biopsy of the clamped tissue through the apparatus, respectively.

Detailed Description of the Invention

Referring to FIGS. 1-4, a system 8 includes a clamping apparatus 10 having a first member 12 and a second member 14 which is spaced apart from the first member. Member 12 has a lower surface 16 opposing an upper surface 18 of member 14. At one end of member 12 is connected a mechanism 20 for attaching or coupling apparatus 10 to a confocal imaging system 22 of system 8. For purposes of illustration, confocal imaging system 22 is represented by a cylinder 23 which contains confocal optics, such as an objective focusing lens. Confocal imaging system 22 is described in related European Patent Publication EP0821256A2, published 28 January 1998. While confocal imaging is the preferred embodiment, system 22 may also represent a system using other imaging modalities, such as optical coherence tomography, described for example in Schmitt et al., "Optical characterization of disease tissues using low-coherence interferometry," Proc. of SPIE, Volume 1889 (1993), or two-photon microscopy, described for example in U.S. Patent No. 5,034,613, to Denk et al., or deconvolution confocal microscopy, described for example in Kesterson, et al., "Confocal Microscope Capability with Desktop Affordability," Advanced Images, Oct. 1991, pages 23-24, or fluorescent imaging. The

objective focusing lens in system 22 may be part of a fixed station or a portable confocal imaging system.

Mechanism 20 has an annular receptacle 24, such as a ring, having a lower member or template 28. Receptacle 24 receives cylinder 23, while pins 26, for example three, are threaded into the sides of receptacle 24, such that they can be extended into grooves or openings 27 in cylinder 23, thereby fixing the position of the confocal imaging system 22 to apparatus 10. (Openings 27 and cylinder 23 are shown in receptacle 24 of FIG. 1 as dashed lines.) Mechanism 20 is described, for example, in related European Patent Publication EP0821256A2, published 28 January 1998. Template 28 has an aperture 30 through which the confocal imaging system, i.e., confocal optics, images the tissue. Aperture 30 may, for example, be several millimeters in diameter. As best shown in FIG. 3, an annular recess 34 in the bottom surface 29 of template 28 is in communication with aperture 30, in other words, a bore of smaller to larger diameter from aperture 30 and recess 34, respectively, widens to provide an annular recess 34 at surface 29. (Recess 34 is also shown in dotted lines in FIG. 2.) In recess 34, a window 32 of a thin transparent material, such as plastic or glass, is fitted. For example, window 32 may be a thin plate of glass, suitably about 0.1-0.2 mm thick. Window 32 is sized such that it fits into annular recess 34, however, window 32 may be square in shape, thus requiring grooves in recess 34 to receive the corners of the window. Window 32, for example, may be a coverslip as conventionally used in preparation of slides for a typical optical microscope. Surface 29 of template 28 has a textured surface, which is represented by raised ridges 36.

In apparatus 10, an opposing member 40 has an upper surface 41 which opposes surface 29 of mechanism 20. Opposing member 40 is connected to an end 14b of member 14. Upper surface 41 has a textured surface, which is represented by raised ridges 38 (see FIG. 4). Surface 41 optionally may have a layer of deformable compliant material, such as urethane. Member 40 may be a disk, as illustrated in the figures, however the shape of member 40 may depend on the patient body part having the tissue to be located between surfaces 29 and 41. For example, member 40 may be split into two or more sections, like a fork, to avoid interfering with other tissue near the body part, such as when the tissue to be imaged is in the middle of the tongue. Other shapes for member 40 may also be used, such as oblong or rectangle. Accordingly, member 40 may be any structure providing a

- 5 -

surface 41 which opposes surface 29 and can provide pressure and traction against a patient body part clamped between surfaces 29 and 41, as described below. Members 12 and 14, receptacle 24, and member 40 may be made of stainless-steel or plastic. Receptacle 24 may be a separate component that is joined (screwed or welded) to the assembly of member 12.

A clamping mechanism in apparatus 10 clamps tissue in the space between surface 29 of mechanism 20 and surface 41 of member 40. The clamping mechanism includes a hinge provided by a spring 42 to members 12 and 14 at the ends thereof opposite mechanism 20 and member 40, respectively, a turn screw 44 threaded in holes 12a and 14a through members 12 and 14, respectively, and members 12 and 14 connected to mechanism 20 and member 40, respectively. Spring 42 is a flat strip of flexible material (steel, plastic or bronze), and applies a force on members 12 and 14 pushing the members apart from each other. Screw 44 is rotatable to manually adjust the spacing between surfaces 29 and 41, such that tissue can be clamped between surfaces 29 and 41, and released therefrom. Alternatively, the clamping mechanism may be provided by two or more screws, similar to screw 44, threaded through members 12 and 14 for setting the space between surfaces 29 and 41. These screws can be independently adjusted to provide angular adjustment of members 12 and 14 to each other to insure that surfaces 29 and 41 are parallel as they restrain the tissue. Other means for clamping may also be used which are similar to clamps of conventional surgical instruments.

Referring to the example shown in FIGS. 5A and 5B, a tongue 46 having the tissue of a patient to be examined is first inserted between members 12 and 14. To facilitate insertion of tongue 46, an operator turns screw 44 until the space between surfaces 29 and 41 is wider than the thickness of the tongue. With tongue 46 between surfaces 29 and 41 and the area of the tongue to be investigated facing window 32, the tongue is clamped to apparatus 10 by the operator turning screw 44 until the tongue is immobilized with respect to surfaces 29 and 41 without damaging the tissue or causing unnecessary discomfort to the patient. The textured surfaces of surfaces 29 and 41 provide traction against the surfaces of tongue 46 to maintain the tissue area under investigation stable for imaging. When apparatus 10 is clamped to tongue 46, surfaces 29 and 41 of mechanism 20 and member 40, respectively, are substantially parallel to each other. Accordingly, the

- 6 -

downward clamping force of mechanism 20 is substantially parallel to the upward clamping force of member 40 against the surfaces of tongue 46. This is an important feature of the invention since it avoids the tongue from squeezing out of clamping apparatus 10.

The confocal imaging system 22 is attached into receptacle 24 of mechanism 20 using pins 26, as shown in FIG. 1, to provide an integrated assembly of the imaging system 22 and apparatus 10. The attachment may be done most conveniently after the tissue is clamped by apparatus 10, however it may occur before tongue 46 is clamped. Window 32 in surface 29 of mechanism 20 presents a tissue area of the clamped tongue to the confocal imaging optics in system 22, thereby enabling confocal imaging of the tissue beneath the window. The tissue under the window is thus mechanical stabilized to the confocal imaging system 22, which minimize instability in confocal images by reducing the relative motion of tissue with respect to the confocal imaging optics of system 22. Apparatus 10 may also operate without window 32, such that window 32 is removed from recess 34 prior to apparatus 10 being clamped to tissue.

Optionally, a suction mechanism may assist in clamping apparatus 10 to tongue 46, as shown in FIG. 6. The suction mechanism includes a syringe 50 connected through a hose 52 to receptacle 24. An annular opening, or one or more holes, provided in surface 29 of receptacle 24 is in communication with hose 52, such that after apparatus 10 is clamped to tongue 46, pulling plunger 51 of syringe 50 in the direction of arrow 53 suctions any air between surface 29 and the surface of tongue 46 facing surface 29. This results in a vacuum adhering surface 29 and the clamped tissue together, thereby further stabilizing the tongue against window 32.

Referring to FIGS. 7A and 7B, clamping apparatus 10 is shown in which the clamping mechanism is provided by a pneumatic system instead of turn screw 44 (FIG. 1), and members 12 and 14 are part of a single C-shaped member 13 without hinge 42. The pneumatic system includes a bladder 54, which is attached to surface 41, a syringe 58, and a hose 56 connecting syringe 58 to bladder 54. A fluid 57, such as air, water, or the like, can pass through hose 56 between bladder 54 and a cavity 60 in syringe 58. Cavity 60 is defined by the interior of syringe 58 and the head 63 of a plunger 62 in syringe 58.

- 7 -

Plunger 62 is slidable within syringe 58 to change the volume of fluid 57 in both cavity 60 and bladder 54.

As shown in FIG. 7A, when plunger 62 is in a first position, bladder 54 is deflated due to the lack of fluid 57 in bladder 54. In this first position, the tissue, such as tongue 46 of FIG. 5A, may be inserted between mechanism 20 and member 40. Once the tissue is properly positioned under mechanism 20, plunger 62 is pushed by an operator to a second position, as shown in FIG. 7B. This forces some of the fluid 57 in cavity 60 through hose 56 into bladder 54, which causes bladder 54 to inflate and force the tissue against surface 29. Bladder 54 is inflated to sufficiently clamp apparatus 10 to the tissue. Hose 56 may be clamped if needed to prevent back flow of fluid 57 into cavity 60 of syringe 58. Optionally, single or multiple turn screws 44 (FIG. 1) may be used in apparatus 10 in combination with the pneumatic system in which bladder 54, when inflated, provides an additional clamping force upon the tissue.

System 8 is particularly useful for mechanically stabilizing the confocal imaging system 22 to oral tissue, such as the tongue or lip, which may have mucus on its surface. However, apparatus 10 may be sized to accommodate clamping of other tissues of the patient to mechanism 20, such as fingers, the palm of a hand, nails, ears, or male genitalia.

After imaging by confocal system 22, the tissue is released from apparatus 10 by turning turn screw 44 (FIG. 1) in a direction which moves member 40 and mechanism 20 apart from each other, or if the pneumatic system of FIGS. 7A and 7B is used, the tissue is released by pulling plunger 62 back to its first position to deflate bladder 54. However, before the tissue is released from apparatus 10, a biopsy device 64 can be inserted into receptacle 24 to take a biopsy 46(a) of the tissue under window 32, as shown in FIGS. 8A-8C. The biopsy device 64 has a projection 66 which, when positioned in receptacle 24 (FIG. 8B), cuts through window 32 and into the tissue under window 32. However, window 32 may be removed from recess 34 prior to the clamping of apparatus 10 to tissue, such that biopsy device 64 will not need to cut window 32. Blade(s) (not shown) in projection 66 are then extended to cut beneath the tissue surface. As device 64 is removed from receptacle 24 (FIG. 8C) an excised biopsy 46(a) is provided. This biopsy can then be examined by typical pathological techniques to confirm any tissue abnormalities found during imaging of the tissue.

- 8 -

From the foregoing description, it will be apparent that there has been provided an improved system for confocal imaging in tissue. Variations and modifications in the herein described system in accordance with the invention will undoubtedly suggest themselves to those skilled in the art. For example, members 12 and 14, tissue engaging parts 20 and 40, and even spring 42, may be an integrated body molded from plastic or stainless steel. Accordingly, the foregoing description should be taken as illustrative and not in a limiting sense.

What is claimed is:

1. A system for imaging mechanically stabilized tissue comprising:
means for clamping the tissue by application of force to said tissue; and
an imaging system for imaging at least a portion of the clamped tissue coupled to said clamping means to provide therewith an integrated assembly.
2. The system according to Claim 1 wherein said clamping means comprises:
a first member and a second member spaced apart and opposing said first member;
and
means coupled to said first member for attaching said first member to said imaging system.
3. The system according to Claim 2 wherein said attaching means has a first surface facing said tissue, and said clamping means further comprises a third member, coupled to said second member, having a second surface opposing said first surface of said attaching means.
4. The system according to Claim 3 wherein said clamping means further comprises means for adjusting the spacing between said first and second surfaces to force said first and second surfaces against the surfaces of said tissue, thereby clamping said tissue between said first and second surfaces without damaging said tissue.
5. The system according to Claim 4 wherein said adjusting means further comprises means for adjusting the spacing between said first and second surfaces to release said clamped tissue from between said first and second surfaces.
6. The system according to Claim 4 wherein said first and second surfaces are substantially parallel to each other when said first and second surface are clamped to said tissue.

- 10 -

7. The system according to Claim 4 wherein said adjusting means is provided by at least one screw threaded through holes in said first and second members which is rotatable to adjust the spacing between said first and second surfaces.

8. The system according to Claim 3 wherein said clamping means further comprises:
means for inflating a bladder from said second surface of said third member against said tissue to force said tissue against said first surface, thereby clamping said tissue between said first and second surfaces without damaging said tissue.

9. The system according to Claim 8 wherein said bladder is inflated with a fluid sufficient to force said tissue against said first surface.

10. The system according to Claim 9 wherein said inflating means further comprises means for deflating said bladder of said fluid sufficient to release said clamped tissue from between said first and second surfaces.

11. The system according to Claim 9 wherein said fluid is one of liquid and gas.

12. The system according to Claim 3 wherein said second surface has a deformable material facing said tissue.

13. The system according to Claim 3 wherein said first and second surfaces are textured.

14. The system according to Claim 3 wherein said clamping means further comprises means for suctioning air from between said first surface and the surface of said tissue facing said first surface to adhere said first surface to the surface of said tissue.

- 11 -

15. The system according to Claim 3 wherein said third member has one or more sections providing said second surface, said sections being shaped to avoid interference of said clamping means with other tissue near said tissue when said tissue is clamped between said first and second surfaces.

16. The system according to Claim 3 wherein said first and second members are parts of a single member having a closed end in which said closed end opposes said tissue when said tissue is clamped between said first and second surfaces.

17. The system according to Claim 3 wherein said clamping means further comprises a hinge, coupled to said first and second members, which opposes said tissue when said tissue is clamped between said first and second surfaces.

18. The system according to Claim 2 wherein said attaching means comprises a receptacle, coupled to said first member, which is attachable to said imaging system, said receptacle having a template facing said tissue and an aperture in said template through which said imaging system images said clamped tissue when said imaging system is attached to said receptacle.

19. The system according to Claim 18 wherein said template has a recess in communication with said aperture.

20. The system according to Claim 19 wherein said receptacle has a window of a thin transparent material fitted in said recess.

21. The system according to Claim 18 further comprising means for taking a biopsy of said clamped tissue through said aperture when said imaging system is detached from said receptacle.

22. The system according to Claim 1 wherein said imaging system is a confocal imaging system for displaying images of sections of said clamped tissue.

- 12 -

23. An apparatus for positioning tissue to an imaging system comprising:
a first member and a second member spaced apart and opposing said first member;
means coupled to said first member for attaching said apparatus to said imaging system, said attaching means having a first surface facing said tissue;
a third member coupled to said second member having a second surface opposing said first surface of said attaching means; and
means including said first and second members for clamping the tissue between said first and second surfaces.

24. The apparatus according to Claim 23 wherein said clamping means further comprises means for adjusting the spacing between said first and second surfaces to force said first and second surfaces against the surfaces of said tissue, thereby clamping said tissue between said first and second surfaces without damaging said tissue.

25. The apparatus according to Claim 24 wherein said adjusting means further comprises means for adjusting the spacing between said first and second surfaces to release said clamped tissue from between said first and second surfaces.

26. The apparatus according to Claim 24 wherein said first and second surfaces are substantially parallel to each other when said first and second surface are clamped to said tissue.

27. The apparatus according to Claim 24 wherein said adjusting means is provided by at least one screw threaded through holes in said first and second members which is rotatable to adjust the spacing between said first and second surfaces.

28. The apparatus according to Claim 23 wherein said clamping means further comprises:
means for inflating a bladder from said second surface of said third member against said tissue to force said tissue against said first surface, thereby clamping said tissue between said first and second surfaces without damaging said tissue.

- 13 -

29. The apparatus according to Claim 28 wherein said bladder is inflated with a fluid sufficient to force said tissue against said first surface.

30. The apparatus according to Claim 29 wherein said inflating means further comprises means for deflating said bladder of said fluid sufficient to release said clamped tissue from between said first and second surfaces.

31. The apparatus according to Claim 29 wherein said fluid is one of liquid and gas.

32. The apparatus according to Claim 23 wherein said second surface has a deformable material facing said tissue.

33. The apparatus according to Claim 23 wherein said first and second surfaces are textured.

34. The apparatus according to Claim 23 wherein said clamping means further comprises means for suctioning air from between said first surface and the surface of said tissue facing said first surface to adhere said first surface to the surface of said tissue.

35. The apparatus according to Claim 23 wherein said third member has one or more sections providing said second surface, said sections being shaped to avoid interference of said clamping means with other tissue near said tissue when said tissue is clamped between said first and second surfaces.

36. The apparatus according to Claim 23 wherein said first and second members are parts of a single member having a closed end in which said closed end opposes said tissue when said tissue is clamped between said first and second surfaces.

- 14 -

37. The apparatus according to Claim 23 wherein said clamping means further comprises a hinge, coupled to said first and second members, which opposes said tissue when said tissue is clamped between said first and second surfaces.

38. The apparatus according to Claim 23 wherein said attaching means further comprises a receptacle, coupled to said first member, which is attachable to said imaging system, said receptacle having a template facing said tissue and an aperture in said template through which said imaging system images said clamped tissue when said imaging system is attached to said receptacle.

39. The apparatus according to Claim 38 wherein said template has a recess in communication with said aperture.

40. The apparatus according to Claim 39 wherein said receptacle has a window of a thin transparent material which is fitted in said recess.

41. The apparatus according to Claim 38 further comprising means for taking a biopsy of said clamped tissue through said aperture when said imaging system is detached from said receptacle.

42. The apparatus according to Claim 23 wherein said imaging system is a confocal imaging system for displaying images of sections of said clamped tissue.

43. A method for positioning tissue to an imaging system comprising the steps of:

providing a first member and a second member which is spaced apart and opposes said first member;

coupling said first member to said imaging system with the aid of a receptacle attachable to said imaging system, in which said receptacle presents a first surface facing said tissue;

- 15 -



coupling said second member to a third member which presents a second surface opposing said first surface; and



clamping the tissue between said first and second surfaces in which said imaging system images said clamped tissue through an aperture in said receptacle when said imaging system is attached to said receptacle.



44. The method according to Claim 43 wherein said clamping step further comprises the step of:

adjusting the spacing between said first and second surfaces to force said first and second surfaces against the surfaces of said tissue without damaging said tissue.

45. The method according to Claim 43 wherein said first and second surfaces are substantially parallel to each other when said first and second surface are clamped to said tissue.










FIG. 6

SUBSTITUTE SHEET (RULE 26)





FIG. 7A

SUBSTITUTE SHEET (RULE 26)



SUBSTITUTE SHEET (RULE 26)




FIG. 8A




FIG. 8B




FIG. 8C

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US98/16976

A. CLASSIFICATION OF SUBJECT MATTER

IPC(6) :A61B 5/00, 5/05
US CL :600/407

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 600/407, 415, 425, 587, 417, 421, 429, 473, 476; 378/37, 62, 63, 195; 128/915

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched
NONE

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)
APS

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X, P ----- Y, P	US 5,730,133 A (GODIK) 24 March 1998, see entire document.	1, 3 ----- 2, 4-7, 13, 14, 17-20, 23-26, 32, 33, 36, 37-39, 42, 43-45
Y	US 4,212,306 A (MAHMUD) 15 July 1980, see entire document.	2, 4-7, 13, 14, 17-20, 23-26, 32, 33, 36, 37-39, 42, 43-45
Y	US 5,056,523 A (HOTCHKISS, JR. et al.) 15 October 1991, see entire document.	22, 41

☒ Further documents are listed in the continuation of Box C. ☐ See patent family annex.

* Special categories of cited documents:	*T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
A document defining the general state of the art which is not considered to be of particular relevance	*X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
E earlier document published on or after the international filing date	*Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	*Z* document member of the same patent family
O document referring to an oral disclosure, use, exhibition or other means	
P document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search

17 SEPTEMBER 1998

Date of mailing of the international search report

22 DEC 1998

Name and mailing address of the ISA/US
Commissioner of Patents and Trademarks
Box PCT
Washington, D.C. 20231

Facsimile No. (703) 305-3230

Authorized officer

BRIAN L. CASLER

Telephone No. (703) 306-3490

Form PCT/ISA/210 (second sheet)(July 1992)*

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US98/16976

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 4,774,961 A (CARR) 04 October 1988.	1-45
A	US 5,371,368 A (ALFANO et al.) 06 December 1994.	1-45
A, P	US 5,772,597 A (GOLDBERGER et al.) 30 June 1998.	1-45

Form PCT/ISA/210 (continuation of second sheet)(July 1992)*

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☒ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☒ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.

THIS PAGE BLANK (USPTO)